

DATA SHEET



DC3 Basic Desktop Charger

Features

- Charges d43, d63, i62, and i63 handsets
- Charging status indicated in telephone display
- Telephone can be used with full functionality while in charger
- Telephone can automatically send absent indication in charger
- Easy to wipe clean

TECHNICAL SPECIFICATIONS

Physical

Dimensions (l × w × h):	95 × 95 × 55 mm
Weight:	170 g (excl. power adapter)
Material:	Case: PC/ABS Rubber feet
Color:	Steel grey and black

Functional

Supply voltage:	100 - 240 V, 50 - 60 Hz AC (adapter), 5 V DC (charger)
Charge current:	Up to 0.65 A (controlled by the handset)


Environmental

Operating temperature:	+5°C to +40°C
Storage temperature:	-20°C to +65°C
Enclosure protection:	IP30, IEC EN60529
Immunity to electromagnetic fields:	3 V/m EN61000-4-3
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)


Compliance to European Regulations and Standards

EU directives:	2015/863 (RoHS3) amending 2011/65/EU EMC 2014/30/EU LVD 2014/35/EU
Product marking:	 
Safety:	EN 62368-1
EMC:	EN 55032 (class B), EN 55024, EN 61000-3-2, EN 61000-3-3


Compliance to US Regulations and Standards

Product marking:	
Safety:	UL 62368-1
EMC:	FCC CFR 47 Part 15

Compliance to Canadian Regulations and Standards

Product marking:	
Safety:	CSA 62368-1
EMC:	FCC CFR 47 Part 15

Compliance to Australian and New Zealand Regulations and Standards

Product marking:	
Safety:	IEC 62368-1
EMC:	EN 55032 (class B), EN 55024, EN 61000-3-2, EN 61000-3-3

Specifications are subject to change without notice

Ascom (Sweden) AB

Grimbodalen 2

SE-417 49 Göteborg

Sweden

Phone +46 31 55 93 00

www.ascom.com

ascom